

PRODUCT DATASHEET

Humidity/Temperature Datalogger

Records data on an SD card in Excel® format

For easy transfer to a PC for analysis



Features:

- Dual LCD simultaneously displays Relative Humidity and Temperature readings
- Datalogger date/time stamps and stores readings on an SD card in Excel® format for easy transfer to a PC
- Selectable data sampling rate: 5, 10, 30, 60, 120, 300, 600 seconds or Auto
- Complete with 6 AAA batteries, 2G SD card, Universal AC Adaptor, and mounting bracket





Patent Pending

Distributed by:





99, rue Beranger 92320 Chatillon - France

Tel: +33 (0)1 71 16 17 00 Fax: +33 (0)1 71 16 17 03 www.testoon.com

Range	Resolution	Accuracy (%rdg+digits)
32 to 122°F	0.1°F/°C	±1.8°F
0 to 50°C		±0.8°C
10 to 95%RH	0.1%RH	±4%RH
5, 10, 30, 60, 120, 300, 600 seconds or Auto		
2,000K data using a 2G SD card		
5.2 x 3.1 x 1.3" (132 x 80 x 32mm)		
9.9oz (282g)		
	32 to 122°F 0 to 50°C 10 to 95%RH 5, 10, 30, 60, 120, 3 2,000K data using a 5.2 x 3.1 x 1.3" (1:	32 to 122°F 0.1°F/°C 0 to 50°C 10 to 95%RH 0.1%RH 5, 10, 30, 60, 120, 300, 600 seconds or Auto 2,000K data using a 2G SD card 5.2 x 3.1 x 1.3" (132 x 80 x 32mm)

Ordering Information:

SD500Humidity/Temperature Datalogger

